

# 2K PRO 2

Industrial Strength Protection  
with superb protection from sanitizer damage

FloorTek 2K Pro 2 is a high performance 2 component waterborne polyurethane system for the most rigorous home, commercial, industrial and countertop installations.

PROPERTY	RESULTS	ASTM METHOD
% Solids	64 typical	D 3960
Weight /gallon	8.87 lb	D 1475
VOC	48 g/L	D 3960
Pot Life	2 - 4 hours	NA
Recoat Time	6 - 4 hours	NA
Set to Touch	2 hours	D 1650
Print Free Time	12 hours	D 1650
Pencil Hardness	5 hours	D 3363
Direct Impact Resistance	>160 in/lbs	G 14 - 88
Indirect Impact resistance	>160 in/lbs	G 14 - 88
Abrasion Resistance (CS-17 Disk, 1000 gm/ 1000	20 mg loss	D 4060
<b>Chemical Resistance</b>		
10 % Hydrochloric Acid	No Effect	D 1308-87
25% Nitric Acid	Film Destroyed	D 1308-87
10 minute spot test	No Effect	
20 minute spot test	8/few blisters	
30 minute spot test	8/med blisters	
10% Sulfuric Acid	No Effect	D 1308-87
10% Ammonia	8 F Blisters	
10 minute spot test	No Effect	
20 minute spot test	No Effect	
30 minute spot test	Slight softening/recovers	
Saturated Sugar Solution	No Effect	D 1308-87
Saturated Salt Solution	No Effect	D 1308-87
Methanol	No Effect	D 1308-87
Butanol	Slight softening/recovers	D 1308-87
Mineral Spirits	No Effect	D 1308-87
Gasoline	No Effect	D 1308-87
Xylene	No Effect	D 1308-87
Motor Oil	No Effect	D 1308-87
Clorox	No Effect	D 1308-87

**FloorTek 2K Pro 2** imparts twice the abrasion resistance of standard urethanes and 4 times that of typical epoxies. Performance characteristics including high UV, heat and chemical resistances make 2K Pro 2 the ideal finish coat for a wide range of installations such as offices, countertops, retail stores, hospitals, hotels, schools and senior living residences.

Installation of FloorTek 2K Pro 2 over an ATG primer (FloorTek Epoxy Gen 3 or FloorTek 6 Nanocoat) will provide the highest durability surface. Design objectives in color can be achieved with FloorTek Dyes added to FloorTek primers and coatings.

FloorTek 2K Pro 2 requires precise skilled application which will achieve exceptional results on high demand industrial settings, engineered concrete, tile, dimensional stone and other architectural building materials.

2K Pro 2 is available in extra low gloss, low gloss and gloss. An antiskid surface is available.

Coverage is ~400 sq. ft./ gallon

## **ATG Labs, Inc.**

1407 Grand Ave.

Columbia, MO 65203

573-442-4821 [atgsales@socket.net](mailto:atgsales@socket.net)